

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870642.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP54
Response value luminosity (lx)	10 - 2000
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	Yes
No	
Remote operation	Yes
With remote control	No
Width (mm)	80
Height (mm)	15
Diameter (mm)	80
Built-in width (mm)	67
(mm)	49
Built-in depth (mm)	49
Built-in diameter (mm)	67
Built-in size (mm)	67
Max. mounting height (m)	5
Max. reach sideways (m)	6
Diameter reach on floor (m)	12
(m)	16
Number of switching zones	2
Passive infrared	
Integrated	
DALI	
Bridging switch	Yes
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	AC
Min. switch-on time (s)	60
Max. duty cycle (min)	60
Nominal voltage (V)	220 - 240
Max. presence range (m ²)	460
Scan angle (°)	360



(W)	0.5
Connection type	Screwed terminal
Frequency (Hz)	50 - 60
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Teach-function for response value luminosity	Yes
With connection cable	No
Yes	
(m ²)	120
(m ²)	200
10 - 2000	
Yes	
Yes	
Dim function with dimmer basic element	Yes
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Yes	
No	
Yes	
Transparent	No
IFTTT support available	No