

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870935 - IB-PIR-ECO-WH-WIE

/productimages/870935.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

| | |
|--|-------------------------|
| Model | Presence detector |
| Passive infrared | |
| Technique | Passive infrared |
| Constant light control | No |
| HVAC-control | No |
| Forced switch off | No |
| Animal zone | No |
| Integrated | |
| Length of connection cable (mm) | 400 |
| Relay | |
| Networkable | No |
| Suitable for wall mounting | No |
| Optimum mounting height (m) | 2.5 |
| Bridging switch | No |
| Max. reach sideways (m) | 3.5 |
| (VA) | 800 |
| Max. reach frontally (m) | 2 |
| Diameter reach on floor (m) | 7 |
| (W) | 800 |
| Suitable for wireless transmission | No |
| Remote operation | No |
| 25 | |
| With remote control | No |
| Response value sensitivity adjustable | No |
| Response value luminosity adjustable | Yes |
| (W) | 2000 |
| Teach-function for response value luminosity | Yes |
| Dim function with dimmer basic element | No |
| Mounting method | Flush mounted (plaster) |
| Max. mounting height (m) | 4 |
| Material | Plastic |
| Material quality | Thermoplastic |
| Surface protection | Lacquered |
| Surface finishing | Matt |
| Colour | White |
| RAL-number (similar) | 9016 |
| Transparent | No |
| Degree of protection (IP) | IP20 |
| Voltage type | AC |
| Min. switch-on time (s) | 30 |
| Max. duty cycle (min) | 30 |
| No | |
| Detection angle horizontal (°) | 5 - 360 |

| | |
|---------------------------------------|-----------|
| (mm) | 65 |
| Response value luminosity (lx) | 10 - 2000 |
| Max. switching power (W) | 2000 |
| Built-in size (mm) | 63 |
| Number of switching zones | 1 |
| Max. starting current (A) | 800 |
| Substation input | No |
| Frequency (Hz) | 50 - 60 |
| Scan angle (°) | 360 |
| Max. presence range (m ²) | 50 |
| Suitable for ceiling mounting | Yes |
| Connection type | Other |
| With connection cable | Yes |
| Anti-bacterial treatment | No |
| Width (mm) | 80 |
| Height (mm) | 5 |
| Diameter (mm) | 80 |
| Built-in depth (mm) | 67 |
| Built-in diameter (mm) | 65 |
| Max. switching power LED (W) | 600 |
| Compatible with Apple HomeKit | No |
| Yes | |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |
| Nominal voltage (V) | 220 - 240 |
| (V) | 220 - 240 |
| 1 make contact (NO) | |
| Yes | |
| (m) | 8 |
| (m ²) | 40 |
| (m ²) | 64 |
| 6 | |
| No | |
| Yes | |
| Compatible with Casambi | No |