

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870936.jpg

Package type: CT á 1 pce



### PRODUCT SPECIFICATIONS:

|                                       |                         |
|---------------------------------------|-------------------------|
| Mounting method                       | Flush mounted (plaster) |
| Ceiling                               |                         |
| Degree of protection (IP)             | IP20                    |
| Response value luminosity (lx)        | 10 - 2000               |
| HVAC-control                          | No                      |
| Optimum mounting height (m)           | 2.5                     |
| Model                                 | Movement sensor         |
| Constant light control                | No                      |
| No                                    |                         |
| Remote operation                      | No                      |
| With remote control                   | No                      |
| Width (mm)                            | 80                      |
| Height (mm)                           | 5                       |
| Diameter (mm)                         | 80                      |
| (mm)                                  | 65                      |
| Built-in depth (mm)                   | 67                      |
| Built-in diameter (mm)                | 65                      |
| Built-in size (mm)                    | 63                      |
| Max. mounting height (m)              | 4                       |
| Max. reach sideways (m)               | 3.5                     |
| Max. reach frontally (m)              | 2                       |
| 25                                    |                         |
| Diameter reach on floor (m)           | 7                       |
| (m)                                   | 8                       |
| (W)                                   | 2000                    |
| (VA)                                  | 800                     |
| (W)                                   | 800                     |
| Number of switching zones             | 1                       |
| Passive infrared                      |                         |
| Integrated                            |                         |
| Relay                                 |                         |
| Bridging switch                       | No                      |
| Response value sensitivity adjustable | No                      |
| Response value luminosity adjustable  | Yes                     |
| Colour                                | White                   |
| RAL-number (similar)                  | 9016                    |
| Material                              | Plastic                 |
| Material quality                      | Thermoplastic           |
| Surface protection                    | Lacquered               |
| Surface finishing                     | Matt                    |
| Voltage type                          | AC                      |
| Max. starting current (A)             | 800                     |

|  |           |
|--|-----------|
| Min. switch-on time (s)                      | 30        |
| Max. duty cycle (min)                        | 30        |
| Detection angle horizontal (°)               | 5 - 360   |
| Nominal voltage (V)                          | 220 - 240 |
| Max. switching power (W)                     | 2000      |
| Max. switching power LED (W)                 | 600       |
| Max. presence range (m <sup>2</sup> )        | 50        |
| 6  |           |
| Scan angle (°)                               | 360       |
| Connection type                              | Other     |
| Substation input                             | No        |
| Frequency (Hz)                               | 50 - 60   |
| No   |           |
| Suitable for ceiling mounting                | Yes       |
| Suitable for wall mounting                   | No        |
| Suitable for wireless transmission           | No        |
| Forced switch off                            | No        |
| Teach-function for response value luminosity | Yes       |
| With connection cable                        | Yes       |
| Yes  |           |
| 1 make contact (NO)                          |           |
| Yes  |           |
| (m <sup>2</sup> )                            | 40        |
| (m <sup>2</sup> )                            | 64        |
| Yes  |           |
| Dim function with dimmer basic element       | No        |
| Networkable                                  | No        |
| Compatible with Apple HomeKit                | No        |
| Compatible with Casambi                      | No        |
| Compatible with Google Assistant             | No        |
| Compatible with Amazon Alexa                 | No        |
| No   |           |
| Animal zone                                  | No        |
| Transparent                                  | No        |
| IFTTT support available                      | No        |
| Anti-bacterial treatment                     | No        |