

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870942.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

|                                       |                         |
|---------------------------------------|-------------------------|
| Mounting method                       | Flush mounted (plaster) |
| Ceiling                               |                         |
| Degree of protection (IP)             | IP40                    |
| Response value luminosity (lx)        | 5 - 10000               |
| HVAC-control                          | Yes                     |
| Optimum mounting height (m)           | 2.5                     |
| Model                                 | Movement sensor         |
| Constant light control                | No                      |
| Yes                                   |                         |
| Remote operation                      | No                      |
| With remote control                   | No                      |
| (mm)                                  | 111                     |
| Width (mm)                            | 80                      |
| Height (mm)                           | 16                      |
| Diameter (mm)                         | 80                      |
| (mm)                                  | 50                      |
| Built-in depth (mm)                   | 38                      |
| Built-in diameter (mm)                | 65                      |
| Built-in size (mm)                    | 65                      |
| (m)                                   | 1                       |
| Length of connection cable (mm)       | 400                     |
| Max. mounting height (m)              | 5                       |
| Max. reach sideways (m)               | 3                       |
| 16                                    |                         |
| Diameter reach on floor (m)           | 6                       |
| (m)                                   | 8                       |
| (W)                                   | 2300                    |
| (VA)                                  | 1000                    |
| Number of switching zones             | 1                       |
| Passive infrared                      |                         |
| Relay                                 |                         |
| Response value sensitivity adjustable | Yes                     |
| Response value luminosity adjustable  | Yes                     |
| Colour                                | White                   |
| RAL-number (similar)                  | 9010                    |
| Material                              | Plastic                 |
| Material quality                      | Thermoplastic           |
| Surface protection                    | Lacquered               |
| Surface finishing                     | Matt                    |
| Voltage type                          | AC                      |
| Max. starting current (A)             | 800                     |
| Min. switch-on time (s)               | 6                       |

|  |           |
|--|-----------|
| Max. duty cycle (min)                  | 30        |
| Detection angle horizontal (°)         | 30 - 360  |
| Nominal voltage (V)                    | 220 - 240 |
| Max. switching power (W)               | 2000      |
| (st)                                   | 2         |
| Max. presence range (m <sup>2</sup> )  | 50        |
| Scan angle (°)                         | 360       |
| (W)                                    | 0.8       |
| Connection type                        | Other     |
| Frequency (Hz)                         | 50 - 60   |
| Suitable for ceiling mounting          | Yes       |
| Suitable for wall mounting             | No        |
| Suitable for wireless transmission     | No        |
| Forced switch off                      | No        |
| With connection cable                  | Yes       |
| Yes                                    |           |
| Yes                                    |           |
| (m <sup>2</sup> )                      | 30        |
| (m <sup>2</sup> )                      | 50        |
| Yes                                    |           |
| Dim function with dimmer basic element | No        |
| Networkable                            | No        |
| Compatible with Casambi                | No        |
| Compatible with Google Assistant       | No        |
| Compatible with Amazon Alexa           | No        |
| No                                     |           |
| No                                     |           |
| Transparent                            | No        |
| IFTTT support available                | No        |