

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870950 - PLF-IB-PIR/Q-Wi

Aanwezigheidsdetector Plafond Inbouw

/productimages/870950.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	Yes
HVAC-control	No
Forced switch off	No
RJ12	
Relay	
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
Bridging switch	Yes
Max. reach sideways (m)	4
(VA)	500
Diameter reach on floor (m)	8
Suitable for wireless transmission	No
Remote operation	Yes
15	
With remote control	No
(VA)	1000
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	2000
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP40
Voltage type	AC
Min. switch-on time (s)	10
(mm)	140
Max. duty cycle (min)	30
Detection angle horizontal (°)	30 - 360
(mm)	53
(m)	1
Response value luminosity (lx)	5 - 10000
Yes	
Max. switching power (W)	2000
(W)	1.2



Built-in size (mm)	65
Number of switching zones	1
Max. starting current (A)	800
Control current (mA)	100
Frequency (Hz)	50 - 60
Scan angle (°)	360
Max. presence range (m ²)	50
Suitable for ceiling mounting	Yes
Connection type	Other
With connection cable	Yes
Width (mm)	80
Height (mm)	19
Diameter (mm)	80
Built-in depth (mm)	34
Built-in diameter (mm)	65
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	220 - 240
Yes	
Yes	
(m)	8
(m ²)	50
(m ²)	50
No	
No	
Yes	
Compatible with Casambi	No