

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870974.jpg

**Aanwezigheidsdetector Plafond Inbouw**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP44
Response value luminosity (lx)	5 - 10000
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	No
With remote control	No
Width (mm)	111.5
Height (mm)	24
Diameter (mm)	111.5
(mm)	26
Built-in depth (mm)	35
Built-in diameter (mm)	65
Built-in size (mm)	65
Max. mounting height (m)	3
Max. reach sideways (m)	3
10	
Diameter reach on floor (m)	6
(m)	7
(W)	2000
(VA)	500
Number of switching zones	1
Passive infrared	
Integrated	
Relay	
(VA)	900
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	AC
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 360

Nominal voltage (V)	220 - 240
Max. switching power (W)	2200
Max. presence range (m <sup>2</sup> )	50
Scan angle (°)	360
(W)	0.8
Connection type	Other
Frequency (Hz)	50 - 60
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
Forced switch off	No
With connection cable	Yes
Yes	
1 make contact (NO)	
Yes	
(m <sup>2</sup> )	40
Yes	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
No	
Transparent	No
IFTTT support available	No