

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870975 - PLF-INB-UNI-24M-WIE

Aanwezigheidsdetector Plafond Inbouw

870550.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP54
Response value luminosity (lx)	10 - 2000
HVAC-control	Yes
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	Yes
With remote control	No
Width (mm)	105
Height (mm)	44.5
Diameter (mm)	105
(mm)	43.5
Built-in depth (mm)	43.5
Built-in diameter (mm)	68
Built-in size (mm)	68
Max. reach sideways (m)	12
Max. reach frontally (m)	3
Diameter reach on floor (m)	24
(m)	24
(W)	2300
Number of switching zones	1
Passive infrared	
Integrated	
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Nominal voltage (V)	220 - 240
Max. switching power (W)	2300
Max. presence range (m ²)	465
6	
Scan angle (°)	360
(W)	0.5
Connection type	Other
Frequency (Hz)	50 - 60

Yes	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Suitable for wireless transmission	No
With connection cable	Yes
Yes	
Yes	
(m ²)	465
(m ²)	465
10 - 2000	
Yes	
Yes	
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
No	
Transparent	No
IFTTT support available	No