

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

870470.jpg

Package type: CT á 1 pce

## PRODUCT SPECIFICATIONS:

|                                       |                         |
|---------------------------------------|-------------------------|
| Mounting method                       | Flush mounted (plaster) |
| Ceiling                               |                         |
| Degree of protection (IP)             | IP20                    |
| Response value luminosity (lx)        | 10 - 2000               |
| HVAC-control                          | No                      |
| Optimum mounting height (m)           | 6.5                     |
| Model                                 | Movement sensor         |
| Constant light control                | No                      |
| No                                    |                         |
| Remote operation                      | No                      |
| With remote control                   | No                      |
| Width (mm)                            | 80                      |
| Height (mm)                           | 5                       |
| Diameter (mm)                         | 80                      |
| (mm)                                  | 65                      |
| Built-in depth (mm)                   | 67                      |
| Built-in diameter (mm)                | 63                      |
| Built-in size (mm)                    | 63                      |
| Max. mounting height (m)              | 6.5                     |
| Max. reach sideways (m)               | 4.15                    |
| Max. reach frontally (m)              | 4.15                    |
| 25                                    |                         |
| (W)                                   | 2000                    |
| (VA)                                  | 800                     |
| (W)                                   | 600                     |
| Number of switching zones             | 1                       |
| Passive infrared                      |                         |
| Integrated                            |                         |
| Relay                                 |                         |
| Staircase monitoring                  | Yes                     |
| Bridging switch                       | No                      |
| Response value sensitivity adjustable | No                      |
| Response value luminosity adjustable  | Yes                     |
| Colour                                | White                   |
| RAL-number (similar)                  | 9016                    |
| Material                              | Plastic                 |
| Material quality                      | Thermoplastic           |
| Surface protection                    | Lacquered               |
| Surface finishing                     | Matt                    |
| Voltage type                          | AC                      |
| Max. starting current (A)             | 800                     |
| Min. switch-on time (s)               | 30                      |

|  |                  |
|--|------------------|
| Max. duty cycle (min)                        | 30               |
| Detection angle horizontal (°)               | 5 - 360          |
| Nominal voltage (V)                          | 220 - 240        |
| Max. switching power (W)                     | 2000             |
| Max. switching power LED (W)                 | 600              |
| Max. presence range (m <sup>2</sup> )        | 86.5             |
| 6  |                  |
| Scan angle (°)                               | 360              |
| Connection type                              | Screwed terminal |
| Substation input                             | No               |
| Frequency (Hz)                               | 50 - 60          |
| Suitable for ceiling mounting                | Yes              |
| Suitable for wall mounting                   | No               |
| Suitable for wireless transmission           | No               |
| Forced switch off                            | No               |
| Teach-function for response value luminosity | Yes              |
| With connection cable                        | No               |
| Yes  |                  |
| Yes  |                  |
| Yes  |                  |
| Ambient temperature (°C)                     | -10 - +40        |
| Dim function with dimmer basic element       | No               |
| Networkable                                  | Yes              |
| Compatible with Apple HomeKit                | No               |
| Compatible with Casambi                      | No               |
| Compatible with Google Assistant             | No               |
| Compatible with Amazon Alexa                 | No               |
| With alarm function                          | No               |
| No   |                  |
| Animal zone                                  | Yes              |
| Transparent                                  | No               |
| IFTTT support available                      | No               |
| Yes  |                  |
| Anti-bacterial treatment                     | No               |