

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

876684 - LED-OPB-CW

Led spots, opbouw

/productimages/876684.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Surface mounting
Dimmable	Yes
Colour temperature (K)	6000 - 6000
Colour of light adjustable	No
Rated luminous flux according to IEC 62722-2-1 (lm)	215
(lm)	0 - 215
(lm/W)	0 - 102
Nominal current (mA)	0 - 700
Nominal voltage (V)	3 - 3
Voltage type	DC
Max. system power (W)	2.1
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Medium beam 21-40°
Beam angle (°)	35
Width (mm)	32
Height/depth (mm)	37
Outer diameter (mm)	19
Housing colour	Aluminium
Degree of protection (IP), front side	IP44
Other	
Degree of protection (IP)	IP20
Suitable for ceiling mounting	Yes
Suitable for wall mounting	Yes
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	2.1 - 2.1
Adjustability	Swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Optics	Lens
(cm)	100
Light distributor	Focal lens
Light outlet	Direct

Number of poles	2
With mounting bracket	Yes
With presence indicator	No