

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

876823 - LED-DRV40WI-D

Leddriver constante stroom


</productimages/876823.jpg>

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	1 - 10 V
Output power (W)	1 - 40
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	15 - 32
Input voltage (V)	100 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	300 - 1400
Yes	
Resistor	
(mA)	1400
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	157
Width (mm)	42
Height (mm)	32
0.97	
Ambient temperature (°C)	-25 - +60
Grey	
No	
Number of channels	1
(W)	40
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
(h)	50000
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
IFTTT support available	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	Yes
Compatible with Apple HomeKit	No



Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	Yes
Dimming LineSwitch	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming programmable	No
Dimming Sine Wave Reduction	No
Dimming DMX	No
Dimming mains voltage modulation	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No
Dimming 0-10 V	No
No	