

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

890115 - DRD-PAF-ZG-200

890105.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Assembly arrangement	Basic element
Protocol	Zigbee
Type of load	Universal and LED Retrofit
Nominal voltage (V)	100 - 240
Frequency (Hz)	50 - 60
Nominal power resistive load (W)	0 - 400
Dimming phase cut-off	Yes
Mounting method	DRA (DIN-rail adapter)
Suitable for degree of protection (IP)	IP20
Material	Plastic
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Applicable with button	Yes
Light value memory	Yes
Applicable with transmission button	No
Applicable with infrared button	No
Material quality	Thermoplastic
Dimming phase cut-on	No
Connection type	Screwed terminal
Width (mm)	18
Height (mm)	90
Depth (mm)	66
Max. switching power LED (W)	200
Compatible with Google Assistant	Yes
Compatible with Amazon Alexa	Yes
Not applicable	
(W)	0 - 400
Wireless	Yes
Min. brightness controllable	Yes
Substation input	Yes
Transparent	No
Serial dimmer	No