

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

891028 - DIM PAF 5-600

Dimmers

Package type: CT á 1 pce

/productimages/891028.jpg



PRODUCT SPECIFICATIONS:

| | |
|--|----------------------------|
| Assembly arrangement | Basic element |
| Method of operation | Turn/push button |
| Protocol | Phase cut-off |
| Type of load | Universal and LED Retrofit |
| Nominal voltage (V) | 220 - 240 |
| Frequency (Hz) | 50 - 50 |
| Nominal power resistive load (W) | 5 - 600 |
| Dimming phase cut-off | Yes |
| (st) | 40 |
| (st) | 40 |
| Mounting method | Flush mounted (plaster) |
| Type of fastening | Mounting with screw |
| Suitable for degree of protection (IP) | IP20 |
| Device height (mm) | 71 |
| Device width (mm) | 71 |
| Axis length (mm) | 10 |
| Material | Metal |
| Surface finishing | Glossy |
| Colour | Aluminium |
| Light value memory | Yes |
| App control via Bluetooth | No |
| Dimming phase cut-on | No |
| No | |
| Nominal power capacitive load (VA) | 5 - 600 |
| Connection type | Screwed terminal |
| Depth (mm) | 25 |
| Min. depth of built-in installation box (mm) | 27 |
| Max. switching power LED (W) | 600 |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Min. brightness controllable | Yes |
| Substation input | Yes |
| Transparent | No |
| Serial dimmer | No |