

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 891040 - D-PAF-315

Dimmers

Package type: CT á 1 pce

/productimages/891040.jpg



**PRODUCT SPECIFICATIONS:**

Assembly arrangement	Basic element
Method of operation	Turn/push button
Serial dimmer	No
Protocol	Phase cut-off
Type of load	Capacitive load
Light value memory	Yes
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with screw
Material	Metal
Surface finishing	Glossy
Colour	Aluminium
Transparent	No
Suitable for degree of protection (IP)	IP20
Nominal voltage (V)	220 - 240
Frequency (Hz)	50 - 50
Device width (mm)	71
Device height (mm)	71
App control via Bluetooth	No
No	
Dimming phase cut-off	Yes
(st)	18
Nominal power resistive load (W)	20 - 315
(st)	18
Nominal power capacitive load (VA)	20 - 315
Axis length (mm)	10
Connection type	Push-in clamp
Min. depth of built-in installation box (mm)	40
Max. switching power LED (W)	315
Compatible with Apple HomeKit	No
Depth (mm)	40
Compatible with Google Assistant	No
Power supply system	Mains voltage
Min. brightness controllable	Yes