

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 891046 - D-PAF-200EU-10

Dimmers

/productimages/891046.jpg

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Assembly arrangement	Basic element
Method of operation	Turn/push button
Protocol	Phase cut-off
Type of load	Universal and LED Retrofit
Nominal voltage (V)	220 - 240
Frequency (Hz)	50 - 50
Nominal power resistive load (W)	1 - 200
Dimming phase cut-off	Yes
(st)	15
(st)	15
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with screw
Suitable for degree of protection (IP)	IP20
Device height (mm)	71
Device width (mm)	71
Axis length (mm)	10
Material	Metal
Surface finishing	Glossy
Colour	Aluminium
Light value memory	Yes
App control via Bluetooth	No
Dimming phase cut-on	No
Yes	
Nominal power capacitive load (VA)	1 - 200
Connection type	Push-in clamp
Depth (mm)	33
Min. depth of built-in installation box (mm)	35
Max. switching power LED (W)	200
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Min. brightness controllable	Yes
Substation input	Yes
Transparent	No
Serial dimmer	No