

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 891324 - BE-DPAF-250-MOD

891042.jpg

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

Assembly arrangement	Basic element
Method of operation	Configuration dependant
Protocol	Phase cut-off
Type of load	Universal and LED Retrofit
Nominal voltage (V)	207 - 253
Frequency (Hz)	50 - 50
Nominal power resistive load (W)	1 - 250
Dimming phase cut-off	Yes
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with screw
Suitable for degree of protection (IP)	IP20
Device height (mm)	71
Device width (mm)	71
Device depth (mm)	22
Material	Other
Surface finishing	Glossy
Colour	Aluminium
Applicable with button	Yes
Applicable with movement sensor	Yes
Applicable with presence indicator	Yes
Applicable with time switch/timer	Yes
Light value memory	Yes
Applicable with transmission button	No
Applicable with infrared button	No
Material quality	Aluminium
Halogen free	Yes
Surface protection	Untreated
App control via Bluetooth	Yes
Dimming phase cut-on	No
Nominal power capacitive load (VA)	1 - 250
Connection type	Push-in clamp
Core cross section (mm <sup>2</sup> )	1.5 - 2.5
Min. depth of built-in installation box (mm)	25
Max. switching power LED (W)	250
Brand-dependent	
Min. brightness controllable	Yes
Substation input	Yes
Transparent	No
Serial dimmer	No