

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

891330 - BE-DALI-1-25-MOD

891005.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

| | |
|--|-------------------------|
| Assembly arrangement | Basic element |
| Method of operation | Configuration dependant |
| Serial dimmer | No |
| Protocol | DALI |
| Type of load | Other |
| Substation input | No |
| Light value memory | Yes |
| Applicable with button | Yes |
| Applicable with movement sensor | Yes |
| Applicable with presence indicator | Yes |
| Applicable with time switch/timer | Yes |
| Applicable with transmission button | No |
| Applicable with infrared button | No |
| Mounting method | Flush mounted (plaster) |
| Type of fastening | Mounting with screw |
| Material | Other |
| Material quality | Aluminium |
| Halogen free | Yes |
| Surface protection | Untreated |
| Surface finishing | Glossy |
| Colour | Aluminium |
| Transparent | No |
| Suitable for degree of protection (IP) | IP20 |
| Nominal voltage (V) | 207 - 253 |
| Frequency (Hz) | 50 - 50 |
| Device width (mm) | 71 |
| Device height (mm) | 71 |
| Device depth (mm) | 22 |
| App control via Bluetooth | Yes |
| Dimming phase cut-on | No |
| Dimming phase cut-off | No |
| Connection type | Push-in clamp |
| Core cross section (mm ²) | 1.5 - 2.5 |
| Min. depth of built-in installation box (mm) | 25 |
| Brand-dependent | |
| Control current (mA) | 50 |
| Min. brightness controllable | Yes |