

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

891330 - BE-DALI-1-25-MOD

891005.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Assembly arrangement	Basic element
Method of operation	Configuration dependant
Protocol	DALI
Type of load	Other
Nominal voltage (V)	207 - 253
Frequency (Hz)	50 - 50
Dimming phase cut-off	No
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with screw
Suitable for degree of protection (IP)	IP20
Device height (mm)	71
Device width (mm)	71
Device depth (mm)	22
Material	Other
Surface finishing	Glossy
Colour	Aluminium
Applicable with button	Yes
Applicable with movement sensor	Yes
Applicable with presence indicator	Yes
Applicable with time switch/timer	Yes
Light value memory	Yes
Applicable with transmission button	No
Applicable with infrared button	No
Material quality	Aluminium
Halogen free	Yes
Surface protection	Untreated
App control via Bluetooth	Yes
Dimming phase cut-on	No
Connection type	Push-in clamp
Core cross section (mm ²)	1.5 - 2.5
Min. depth of built-in installation box (mm)	25
Brand-dependent	
Control current (mA)	50
Min. brightness controllable	Yes
Substation input	No
Transparent	No
Serial dimmer	No