

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

Krimpous Polyofin In Trekboxen

Package type: CT á 20 Metre

/productimages/946004.jpg



**PRODUCT SPECIFICATIONS:**

|  |                               |
|--|-------------------------------|
| Colour                                   | Yellow                        |
| Inner diameter before heat-shrink (mm)   | 1.2                           |
| Inner diameter after heat-shrink (mm)    | 0.6                           |
| Length (m)                               | 20                            |
| Shrink rate                              | 2:1                           |
| Nominal diameter inch                    | 3/64 inch                     |
| Nominal cross section (mm <sup>2</sup> ) | 0.34 - 1.5                    |
| Wall thickness after shrinking (mm)      | 0.41                          |
| Operating temperature (°C)               | -55 - +135                    |
| (°C)                                     | 100                           |
| Model                                    | Thin-walled                   |
| Material                                 | Crosslinked polyolefin (XLPO) |
| Halogen free                             | Yes                           |
| With inner glue                          | No                            |
| Printable                                | No                            |
| UL approval                              | Yes                           |
| Type                                     | Heat-shrink                   |
| Breakdown voltage (kV)                   | 10                            |
| Self-extinguishing                       | Yes                           |